

# 1501

**iNetVu®**  
by C-COM Satellite Systems Inc.

## TECHNICAL SPECIFICATIONS

The iNetVu® 1501 Drive-Away antenna system is a sleek, simple to operate auto-deploy VSAT terminal which can be mounted on the roof of a vehicle. It is suitable for the most demanding applications. Its reflector optics feature a long focal length for excellent cross-pol performance. All three motorized axes have very low backlash and work together seamlessly with sophisticated integral sensors and the iNetVu® 7710 Controller to ensure excellent pointing accuracy.



### Features

- 1.5m Offset, prime focus, carbon fibre reflector
- Low stow height
- 35 dB crosspol for large carrier uplinking
- Designed to work with the iNetVu® 7710 Controller
- Supports hand cranks when required
- Supports up to 200W Redundant BUC directly on feed arm
- One button, auto-pointing controller acquires any satellite within 2 minutes
- Optimal high-precision antenna pointing
- Includes jog controller functions
- Remote access and operation via network, web and other interfaces
- Modular design makes all major aspects of the antenna field serviceable
- Standard 2 year warranty

### Application Versatility

The 1501 drive-away system is easily configured to provide instant access to satellite communications for any application that requires reliable and/or remote connectivity in a rugged environment. Ideally suited for applications that require a quick, simple set-up typically for industries such as SNG, Disaster Management, Oil & Gas Exploration, Mining, Construction, Mobile Offices and Emergency Services.

**C-COM**  
SATELLITE SYSTEMS INC.

613-745-4110 | 1-877-463-8886 (1-877-iNetVu6)  
[www.c-comsat.com](http://www.c-comsat.com)

Specifications are subject to change

Draft Sept, 2021

# 1501



## TECHNICAL SPECIFICATIONS

### Mechanical

Reflector Size & Material	1.5m Carbon Fibre
Platform Geometry	Elevation over Azimuth
Offset Angle	16.97°
Antenna Optics	One-piece offset feed, prime focus
Azimuth Travel	± 200°
Elevation Look Angle	0° to 90°
Polarization Travel	± 95°
Elevation Deploy Speed	2°/sec
Azimuth Deploy Speed	6°/sec
Peaking Speed	0.2°/sec
Motor Voltage	24 VDC 10 Amp (Max.)

### Environmental

Wind loading	
Operational	72 km/h (45 mph)
Survival	
Deployed	112 km/h (70 mph)
Stowed	225 km/h (140 mph)
Temperature	
Operational	-30° to 55° C (-22° to 131° F)
Survival	-40° to 65° C (-40° to 149° F)
Solar Radiation	1000Kcal/h/m (360 BTU/h/sq. ft.)
Rain	10 cm/h (4 in/h)
Humidity	0-100% (condensing)
Thermal Test per MIL-STD-810F, Method 501.4, High/Low Temperatures	
Vibration Test per MIL-STD-810F, Annex A, Category 4, Truck/Trailer/Tracked	
Shock Test per IEC 60068-2-27	

### Antenna Bands

Transmit Power <sup>(1)</sup>	1 to 400 watt				
Feed	2 Port XPol			• 1 to 125 watt	
	<i>Ku-Linear</i>	<i>C-Linear (Std/INSAT) <sup>(3)</sup></i>	<i>X Band <sup>(3)</sup></i>	<i>Ka - Linear R/O <sup>(3)</sup></i>	
	<b>Receive</b>	<b>Receive</b>	<b>Receive</b>	<b>Receive</b>	<b>Receive</b>
Frequency (GHz)	10.70 - 12.75 <sup>(2)</sup>	3.40 - 4.20 <sup>(2)</sup>	7.25-7.75	17.70 - 21.2 <sup>(2)</sup>	
Optional	10.70 - 11.70	4.50 - 4.80			
Feed Interface	WR75	CPR-229			WR42
Midband Gain Co-Pol (± 0.2dBi)	43.70	33.40			
Antenna Noise Temp. (K)	10° EL = 65 / 20° EL = 58	10° EL = 45 / 20° EL = 40			
Sidelobe Envelope, Co-Pol (dBi)					
1.5° < Θ < 20°	Meets ITU 580, INTELSAT	IESS 601 STD G		DSCS Req.	
20° < Θ < 26.3°	-3.5	-3.5			
26.3° < Θ < 48°	32-25 Log Θ	32-25 Log Θ			
48° < Θ < 180°	-10 (Typical)	-10 (Typical)			
Cross-Polarization on Axis	> 35 dB	> 30 dB			
Within 1dB Beamwidth	> 30 dB	> 26 dB			
Tx/Rx Isolation	> 40 dB	> 60 dB			
VSWR	1.3:1	1.3:1	1.25:1 (Max.)		
	<b>Transmit</b>	<b>Transmit</b>	<b>Transmit</b>	<b>Transmit</b>	
	13.75 - 14.50	5.850 - 6.725	7.90-8.40		
	12.75 - 14.50	6.725 - 7.025			
	WR75	N or CPR-137			
	45.00	37.20			

### Electrical

Rx & Tx Cables	2 RG6 Cables - 10 m (33 ft) each
Control Cables	
Standard	10 m (33 ft) Extension Cable
Optional	Up to 30 m (100 ft) available

### RF Interface

Radio Mounting	Feed arm/Inside vehicle
Coaxial	RG6U F Type
	N Type (optional)
Axis transition	Rotary Joint + Twist-Flex Waveguide

### Physical

Stowed dimensions	L: 214 cm (84.25")	W: 154 cm (60.5")
	H: 40 cm (15.75")	
Reflector Weight	11.3 kg (25 lbs)	
Platform Weight	72.7 kg (160 lbs)	
Total Platform Weight	84 kg (185 lbs)	

### Shipping Weights & Dimensions\*

Platform Crated: 211 cm x 41 cm x 61 cm (83" x 16" x 24"), 118 kg (260 lbs)  
 Reflector Crate: 168cm x 168cm x 48cm (66" x 66" x 19"), 116.3 kg (256 lbs)  
 Total Weight: 234.3 kg (516 lbs)

\*The shipping weights/dims can vary for particular shipments depending on actual system configuration, quantity, packaging materials and special requirements

Notes: <sup>(1)</sup> Depending on size and weight for feed arm mounting limitation <sup>(3)</sup> Call your C-COM sales representative for availability  
<sup>(2)</sup> LNB PLL Type required with stability better than ± 25 KHz <sup>(4)</sup> Offered on platforms only

