

# Transportable Skid 1200/1202

# iNetVu®

by C-COM Satellite Systems Inc.

## TECHNICAL SPECIFICATIONS

The iNetVu Transportable Skid is a robust transportable base which is designed to support the iNetVu 1200 and 1202 antenna system. The skid can be transported using forklifts or hoists making it possible to rapidly deploy the antenna system without the need to mount it on a trailer or a vehicle.



(Shown with the iNetVu 1200 antenna system and shock absorbers)

### Feature

- Welded aluminum construction is rigid, lightweight & robust
- Easily handled by forks from pallet trucks and warehouse lift-trucks to large outdoor vehicles
- Fork access from all 4 sides
- Easily hoistable
- Antenna can be quickly mounted/dismounted
- Ships fully assembled for very fast integration and deployment
- Optional shock absorbers to greatly reduce road damage

### Physical - 1202

Skid w/ system (with shocks)	146 cm x 218 cm x 58 cm (57.5" x 85.9" x 22.8")
Weight: Skid only	78.9 kg (174 lbs)
Weight: Skid w/ system	160.9 kg (355 lbs)



### Physical - 1200

Skid w/ system (without shocks)	146 cm x 218 cm x 66.7 cm (57.5" x 85.9" x 26.25")
Skid w/ system (with shocks)	146 cm x 218 cm x 71.7 cm (57.5" x 85.9" x 28.25")
Weight: Skid only	78.9 kg (174 lbs)
Weight: Skid w/ system	171.5 kg (378 lbs)

### Shipping Weights & Dimensions <sup>(1)</sup>

Skid w/ system + lid: 146 cm x 218 cm x 83 cm  
(57.5" x 85.9" x 32.7"), 235 kg (518 lbs)  
Lid : 45.4 kg (100 lbs)  
Controller + Cables (30ft): 18.1 kg (40 lbs)  
Total shipping weight of Skid w/ lid, system, controller + cables:  
235.5 kg (519 lbs)

Note: <sup>(1)</sup>

The shipping weights/dims can vary for particular shipments depending on actual system configuration, quantity, packaging materials and special requirements



613-745-4110 | 1-877-463-8886 (1-877-iNetVu6)  
[www.c-comsat.com](http://www.c-comsat.com)

Specifications are subject to change

Feb 2022