Transportable Skid 1200+

TECHNICAL SPECIFICATIONS

The iNetVu® Transportable Skid is a robust transportable base which is designed to support the iNetVu® 1200+ antenna system. The skid can be transported using forklifts or hoists making it possible to rapidly deploy the antenna system without the need to mount it on a trailer or a vehicle.



(Shown with the iNetVu® 1200+ antenna system and shock absorbers)

Physical

Skid w/ system (with shocks)

Weight: Skid only Weight: Skid w/ system 146 cm x 218 cm x 62.4 cm (57.5" x 85.9" x 24.6") 78.9 kg (174 lbs) 160.9 kg (355 lbs)

Feature

- Welded aluminum construction is rigid, lightweight & robust
- Easily handled by forks from pallet trucks and warehouse lift-trucks to large outdoor vehicles

ciNetVu°

by C-COM Satellite Systems Inc.

- Fork access from all 4 sides
- · Easily hoistable
- · Antenna can be quickly mounted/demounted
- Ships fully assembled for very fast integration and deployment
- Optional shock absorbers to greatly reduce road damage



Shipping Weights & Dimensions (1)

Skid w/ system + Lid: 146 cm x 218 cm x 83 cm (57.5" x 85.9" x 32.7") Weight: 224.3 Kg (494.5 lbs) Lid weight: 45.4 Kg (100 lbs) Controller + Cable weight: 18.1 Kg (40 lbs) Total shipping weight: 242.4 Kg (534.4 lbs)

Note: (1)

The shipping weights/dims can vary for particular shipments depending on actual system configuration, quantity, packaging materials and special requirements



613-745-4110 | 1-877-463-8886 (1-877-iNetVu6) www.c-comsat.com

Specifications are subject to change

Dec 2024