

# 7715 Controller

**iNetVu®**  
by C-COM

## TECHNICAL SPECIFICATIONS



### Online with the touch of a button

- Simple stand-alone one touch operation to find satellite & stow antenna
- Typical satellite acquisition time in less than 2 minutes
- Ideal for applications that require a quick, simple setup and reliable connection
- Internal DVB-S2X receiver provides modem independence
- Based on an embedded software solution

### Features

- Simultaneous multi-axis movements
- Easy to configure and operate; one touch stand-alone solution
- Single control cable connection to iNetVu® platform
- Front Panel Configurable
- Only works with iNetVu® mobile platforms which are equipped with 7720/7725 on-board module
- Supports DVB-S2X standard frequencies
- Optimal, high-precision antenna pointing
- Remote access and operation via Network, Web and other Interfaces
- Supports inclined orbit satellites
- Integrated with multiple modems
- Works with GPS and GLONASS Satellite Navigation Systems
- Works with OpenAMIP
- Global Position Information available for external devices
- Supported languages by GUI interface: English, French, Arabic, Russian, Swedish, Chinese (Mandarin, Traditional) and Spanish
- Standard 2 year warranty

### Modem Compatibility\*

The DVB-S2X Tuner is an integrated part of all iNetVu® 7715 Controllers. It allows the iNetVu® system the option to find the satellite with and without the use of a satellite modem. Compact and adaptable, this high performance tuner is programmable to any DVB-S2X frequency and allows the user to pre-configure specific satellite options.

**HughesNet**  
HT 2500

**iDirect**  
Evolution/Velocity X7/IQ200

**Comtech/UHP/CEL**  
UHP/CEL-230/240  
SLM-5650B/C2

**Viasat**  
Surfbeam II/PRO  
Viasat EG1000

**Newtec**  
MDM-3100 (standalone)  
MDM 3X00/MDM2510/MDM6000

**Datum Systems**  
M7L/LT

**Gilat**  
Skyedge IIc (Standalone)

**Spacebridge (Advantech)**  
U7400 (S5420)

**ND Satcom**  
SKYWAN 5G

\* Please contact C-COM if you need more information about modem compatibility as these may change without further notice.



### Optional Beacon Receiver

An optional 19" rack mount iNetVu® Beacon Receiver (BR400L) is available and has been integrated to work with the iNetVu® Controllers. This external self contained compact unit detects the power density of the satellite beacon and is connected to the controller via an RS232 serial port interface.

### Optional GPS/GLONASS Compass

An optional GPS/Glonass based compass is available and has been integrated with the iNetVu Controllers. This external compact device can be fitted on roof of vehicle beside the iNetVu platform to provide accurate vehicle heading within 1 degree irrespective of the surrounding magnetic field. The precise heading of the antenna translates to a smaller search window and hence faster satellite acquisitions. Interfaces to the controller via RS-232 serial port.

### Interfaces

RF Rx In	Type F Connector
RF Rx Out	Type F Connector
7720/7725 Port	Circular Metal Connector
Network Interface	RJ45 Connector and WiFi (2.4GHz)
USB 2.0 (Full Speed)	USB Type B Receptacle
Serial Port	DB9 Female Connector
DC In	Circular Amp Connector
GPS	SMA Connector

### Electrical

LNB Power	Disable, 13V, 14V, 18V, 19V @ 500 mA (Max.)
Universal AC Input	100 - 240VAC, 4.0 - 2.0A, 50/60 Hz
DC Input	24VDC @ 15A
Idle Power Consumption	24VDC @ 1A

### Physical

Dimensions	19" 1U Rack Mountable Unit
Standard	H: 4.5cm (1.75") W: 43cm (17.1") D: 28cm (11.0")
Weight	2.7kg (6.0lbs)

### Environmental

Operating Temperature	-20°C to +60°C (-4°F - 140°F)
Storage Temperature	-40°C to +70°C (-40°F - 158°F)

### Certification

FCC Part 15 Class A, CE for Emission & Immunity Standards

### Shipping dimensions

Shipping box: 54 cm x 44 cm x 20 cm (21" x 17" x 8"); 7kg (15 lbs)  
Optional Cases - See Transportable Cases datasheet



# 7715 Controller



## TECHNICAL SPECIFICATIONS

### SEVEN methods of finding satellite with the iNetVu® 7715 Controller

- DVB Search - Searches directly for any DVB-S2X carrier on the target satellite and peaks on it.
- DVB Search, Opposite Polarity – Searches for DVB-S or DVB-S2 or S2X carrier in the opposite polarity on target satellite, then rotates polarization axes and enables transmitter if modem signal attained.
- DVB Search, Reference Satellite with modem - Searches for a DVB-S or DVB-S2 or S2X carrier on ANY configured reference satellite then moves to the target satellite and peaks on modem signal.
- DVB Search, Reference Satellite without modem - Peaks on a reference satellite then uses precise pointing mechanism to locate the target satellite, even when no modem RF or beacon signal is available to peak on.
- RF Automatic Search – The system will stop and search for modem signal when it senses an increase in RF energy received through the DVB tuner as it passes by the target satellite. If the modem signal is found, the system will begin the peak process.
- RF Override Search – The user specifies an RF Threshold such that the system stops when it reaches an area above the threshold and looks for modem signal to peak on.
- Beacon Receiver – The iNetVu® Controller works seamlessly with the optional iNetVu® Beacon Receiver by searching for a specified beacon frequency and then peaks on it (search gain level can be adjusted).

### The iNetVu® 7715 Controller

- Can be operated from a PC application using the USB port or network port or WiFi
- Has built in web interface that can be operated remotely or locally over a network connection
- Can be completely configured from the front panel with a password protected configuration menu
- Protects the platform and its components from damage, using current levels and sensor readings. It includes motion and movement protection as well
- Provides automatic re-peaking if signal degradation occurs
- Works correctly even when deployed while on an incline (in any direction) of up to 15°
- Can search for both DVB-S, DVB-S2/ACM or DVB-S2X carriers
- Supports full automatic and manual control of the iNetVu® Platform
- Allows the users to select from multiple speed levels for both azimuth and elevation movements
- Allows the system to operate unattended in remote locations
- It is able to upload the recorded log information (Maximum of 12 hours) from the controller to the PC for troubleshooting
- Supports full tracking of Inclined Orbit satellites by both signal strength and timed function
- Is capable of powering the LNB with 13-19 Volts, selectable in software
- Provides the option of saving the settings to a configuration file that can be used to configure additional controllers with the same configuration parameters
- Supports both GPS and GLONASS Satellite Navigation Systems
- Supports Electronic Flux Gate Compass for increased speed of acquisition
- Designed and manufactured to the highest standards of quality and reliability by C-COM
- Only works with iNetVu® Mobile antenna platforms which are equipped with 7720/7725 on board module

