

# FLY-98G

**iNetVu®**  
by C-COM Satellite Systems Inc.

## TECHNICAL SPECIFICATIONS

The iNetVu® FLY-98G Flyaway Antenna is a 98 cm satellite antenna system which is a highly portable, self-pointing, auto-acquire unit that is configurable with the iNetVu® 7715 Controller providing fast satellite acquisition within minutes, anytime anywhere. It can be assembled in 10 minutes by one person.

**Thor7 Type Approved and Compliant for use on Avanti Hylas Ka Satellite Services**



### Features

- One-Piece, high surface accuracy, offset feed, steel reflector
- Heavy duty feed arm capable of supporting up to 5kg (10lbs) Ka transceiver
- Designed to work with the iNetVu® 7715 Controller
- Works seamlessly with the world's emerging commercial Ka modems and services
- 2 Axis motorization (Optional - motorized 3rd axis)
- Supports manual control when required
- One button, auto-pointing controller acquires Ka-band satellite within 2 minutes
- Field upgradable to Ku-band
- Captive hardware / Fasteners
- 10 minute assembly by one person, no tools required
- Compact packaging; 3 ruggedized cases
- Supports Global Invacom 98 cm Ka antenna
- Avanti Approved; Thor7 Type Approved; also compliant with Gilat/iDirect/Newtec Ka services
- Standard 2 year warranty



### Application Versatility

If you operate in Ka-band, the FLY-98G system is easily configured to provide instant access to satellite communications for any application that requires reliable and/or remote connectivity in a rugged environment. This next generation Flyaway Ka terminal delivers affordable broadband Internet services (High-speed access, Video & Voice over IP, file transfer, e-mail or web browsing). Ideally suited for industries such as Oil & Gas Exploration, Military Communications, Disaster Management, SNG, Emergency Communications Backup, Cellular Backhaul and many others.

**C-COM**  
SATELLITE SYSTEMS INC.

613-745-4110 | 1-877-463-8886 (1-877-iNetVu6)  
[www.c-comsat.com](http://www.c-comsat.com)

Specifications are subject to change

Jun 2026

44

# FLY-98G

# iNetVu®

by C-COM Satellite Systems Inc.

## TECHNICAL SPECIFICATIONS

### Mechanical

Reflector	98 cm Elliptical Antenna, offset feed
Platform Geometry	Elevation over Azimuth
Deployment Sensors	GPS antenna Compass ± 2° Tilt sensor ± 0.1°
Azimuth	± 175°
Elevation	0 - 90°
Polarization	(± 45°), Circular Auto
Elevation Deploy Speed	Variable, 3°/sec typ.
Azimuth Deploy Speed	Variable 3°/sec typ.
Peaking Speed	0.1°/sec

### Environmental

Wind loading	
Operational (no ballast)	50 km/h (30 mph)
Operational (with ballast)	72 km/h (45 mph)
Temperature	
Operational	-30° to 60° C (-22° to 140° F)
Survival	-40° to 65° C (-40° to 149° F)
Water Ingress Rating	IP-66

### Electrical

Rx & Tx Cables	2 RG6 cables -10 m (33 ft) each	
Control Cables	10 m (33 ft) Ext. Cable	
Standard	up to 60 m (200 ft) available	
Optional		
Frequency (GHz)	Receive	Transmit
3W-XRC	19.20 - 20.20	29.50 - 30.00
(Optional) 3W-XRF	17.80 - 20.20	29.00 - 30.00
(Optional) 3W-TRX0121	18.10 - 20.20	29.00 - 30.00
(Optional) 4W - AN8025	17.70 - 20.20	29.00 - 30.00
(Optional) 4W - AN8023	17.70 - 20.20	28.10 - 29.10
(Optional) 2 Port CP feed	19.40 - 21.20	29.20 - 31.00
Feed Interface (Circular)	RG6	RG6
Midband Gain (+0.2 dBi)	43.80 @19.70 GHz	47.20 @29.75 GHz
Antenna Noise Temp. (K)	30° EL= 62 Max.	
Sidelobe Envelope Co-Pol (dBi)		
100λ / D < Ø < 20°	29 - 25 Log Ø	
20° < Ø < 26.3°	-3.5	
26.3° < Ø < 48°	32-25 Log Ø	
48° < Ø < 180°	-10 (typical)	
Cross-Polarization	> -24 dB	> -22 dB
VSWR	1.3:1	

### RF Interface

Radio Mounting	Feed Arm
Coaxial	RG6U F Type to tripod base

### Ka-Band (R/O Circular)

	Receive
Frequency (GHz)	17.0 - 22.2
Feed Interface dual polarity	WR42

### Physical

Case 1: Reflector	L: 109 cm (43") H: 29 cm (11.5")	W: 109 cm (43") 28.6 Kg (63 lbs)
Case 2: Tripod/Feed arm	L: 122 cm (48") H: 28cm (11")	W: 58 cm (23") 27.7 Kg (61 lbs)
Case 3: Controller/AZ/EL	L: 44.5 cm (17.5") H: 38 cm (15.5")	W: 80 cm (31.5") 34 Kg (75 lbs)

### Motors

Electrical Interface	24VDC	8 Amp (Max.)
----------------------	-------	--------------

### Shipping Weights & Dimensions\*

Skid: 132 cm x 137 cm x 121.9 cm (52" x 54" x 48") 23.1 Kg (51lbs)  
 Total weight of system in cases: 90.3 Kg (199 lbs)  
 Total weight of system in cases on skid: 113.4 Kg (250 lbs)

\* The shipping weights/dims can vary for particular shipments depending on actual system configuration, quantity, packaging materials and special requirements



613-745-4110 | 1-877-463-8886 (1-877-iNetVu6)

www.c-comsat.com

Specifications are subject to change

Jun 2026