

Enclosed Skid 1200/1202



TECHNICAL SPECIFICATIONS

The iNetVu Transportable Enclosed Skid is a robust transportable enclosure which is designed to support the iNetVu 1200 and the 1202 antenna system. The Enclosed Skid can be transported using forklifts or hoists making it possible to rapidly deploy the antenna system without the need to mount it on a trailer or a vehicle. It also allows for stackability for easier space management & warehousing.



Feature

- Welded aluminum construction is rigid, lightweight & robust
- Easily handled by forks from pallet trucks and warehouse lift-trucks to large outdoor vehicles
- Fork access from all 4 sides
- Easily hoistable
- Antenna can be quickly mounted/demounted
- Ships fully assembled for very fast integration and deployment
- Stackable up to 3 units
- One person operation
- Shock absorbers to reduce road damage

Physical

Enclosed Skid w/ system	148 cm x 218 cm x 79 cm (58.3" x 85.9" x 31.1")
Weight - Enclosed Skid w/ system:	245.9 kg (542 lbs)
Weight - Empty Enclosed Skid:	153.3 kg (338 lbs)

Shipping Weights & Dimensions*

Enclosed Skid w/ system & packaging: 148 cm x 218cm x 79 cm
(58.3" x 85.9" x 31.1"), 252.7 kg (557 lbs)
Controller + Cables (30ft): 18.1 kg (40 lbs)

* The shipping weights/dims can vary for particular shipments depending on actual system configuration, quantity, packaging materials and special requirements

